

SAFETY DATA SHEET**Liquitex Gloss Medium & Varnish (Australia)**

According to the National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition
[NOHSC:2011(2003)]

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product name Liquitex Gloss Medium & Varnish (Australia)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Medium for Acrylic Painting

1.3. Details of the supplier of the safety data sheet

Supplier Jasco Pty Ltd.
1-5 Commercial Road,
Kingsgrove
NSW 2208
02 9807 1555

Contact person Regulatory Manager

Manufacturer ColArt Tianjin Art Materials Co Ltd
80 Xianyang Road
Nankai District
Tianjin, 300113
China

+86 222736 7907

+86 222736 2015

1.4. Emergency telephone number

Emergency telephone Australian poisons centre - 13 11 26

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification**

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

2.3. Other hazards**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

mono propylene glycol			1-5%
CAS number: 57-55-6	EC number: 200-338-0	REACH registration number: 01-2119456809-23-xxxx	

Classification	Classification (67/548/EEC or 1999/45/EC)
Not Classified	-

Liquitex Gloss Medium & Varnish (Australia)

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments Any hazardous ingredients are below classification limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container. Store at moderate temperatures in dry, well ventilated area.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Liquitex Gloss Medium & Varnish (Australia)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

mono propylene glycol

Long-term exposure limit (8-hour TWA): WEL 150 ppm 474 mg/m³ total vapour and particulates

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

WEL = Workplace Exposure Limit

8.2. Exposure controls

Appropriate engineering controls

No specific ventilation requirements.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

No specific hand protection noted.

Other skin and body protection

No specific recommendations

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Clear liquid.

Colour

Clear.

Odour

Odourless.

pH

pH (concentrated solution): 8-9

Initial boiling point and range

> 100°C @ 760 mm Hg

Vapour density

> 1

Relative density

1.1 @ 20°C

Solubility(ies)

Miscible with water

9.2. Other information

Other information

Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability

Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid

Avoid excessive heat for prolonged periods of time. Avoid freezing.

Liquitex Gloss Medium & Varnish (Australia)

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

Notes (dermal LD₅₀) Not determined.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not determined.

General information This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

Inhalation May cause respiratory system irritation.

Ingestion May cause discomfort if swallowed.

Skin contact Slightly irritating.

Eye contact Irritating to eyes.

Acute and chronic health hazards No specific health hazards known.

Route of entry Inhalation Skin and/or eye contact.

Medical symptoms Irritation of eyes and mucous membranes.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Acute toxicity - fish Not determined.

Acute toxicity - aquatic invertebrates Not determined.

Acute toxicity - microorganisms Not determined.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Liquitex Gloss Medium & Varnish (Australia)

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

Rail transport notes Not classified.

Sea transport notes Not classified.

Air transport notes Not classified.

14.1. UN number

Not relevant.

14.2. UN proper shipping name

Not relevant.

14.3. Transport hazard class(es)

Not relevant.

14.4. Packing group

Not relevant.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not relevant.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Dangerous Substances Directive 67/548/EEC.
Dangerous Preparations Directive 1999/45/EC.
System of specific information relating to Dangerous Preparations. 2001/58/EC.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

SECTION 16: Other information

Liquitex Gloss Medium & Varnish (Australia)

General information

EMERGENCY CONTACTS

Jasco Pty Ltd	02 9807 1555
Jasco Pty Ltd - Emergency number	13 11 26
Police and Fire Brigade	000
Poisons information centre	13 11 26

Please read instructions / label before using product.

This SDS is prepared in accordance with the Safe Work Australia document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]

Revision date

29/02/2016

Revision

7

Supersedes date

09/12/2014

SDS number

22710

Risk phrases in full

Not classified.
R22 Harmful if swallowed.
R35 Causes severe burns.

The inclusion of EUH208 is supplemental information taken over from DSD/DPD, it is applicable to CLP and not generalised for GHS; EUH208 therefore only applies in the EU at the time of application. The information contained in this Safety Data Sheet is provided in good faith and is believed to be accurate at the date of issuance. Jasco Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for loss or damage related to the supply or use of the information in this Safety Data Sheet. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.