Material Safety Data Sheet

Enkaustikos! Wax Art Supplies

Date of Prep 2-1-2012

DBA Rochester Art Supply, Inc. 3 North Washington Street Rochester New York 14614 Telephone 1-585-263-6931 Contact Michael Lesczinski, President

1. Material/Product Identity

Enkaustikos Wax Medium Manufacture Code Numbers 70128, 70129, 70148, 70149, 70150, 02306-2, 06306-6 Enkaustikos XD Wax Medium 70130, 70131, 02306X-2, 06306X-6

Wax Medium and XD Wax Medium are blends of US Pharmaceutical Grade Beeswax and FDA approved damar gum.

2. Hazardous Ingredients

Hazardous Components: None Physical Hazards: This material may burn, but will not ignite readily. Keep away from all sources of ignition NFPA Hazard Class: Health: 0 Flammability: 1 Reactivity: 0

3. Physical Data

Appearance: Solid Color: Off white-light yellow Solubility in water: negligible Odor: none to slight-characteristic Vapor Pressure (mm Hg): No data Vapor Density (air+1): No Data Boiling Point: >650 Deg. F, 343 Des C Congealing Point: Typically 143 deg. C Specific Gravity: approximately .96 Percent Volatile: Negligible Bulk Density: approximately 5.5 pounds per gallon

4. Fire and Explosive Data

Flash Point: >400 deg. F
Flammable/Explosive limits (%) No Data
Auto ignition: No Data
Burn Rate (solids only) No Data
Flammable Properties: Flash Point: >400 Deg. F, OSHA
Flammable Class: Not regulated, LEL/UEL: No data, Auto ignition temperature: No data, Burn rate (Solids): No Data
Extinguishing Media: dry chemical, foam, water, sand, or earth is recommended
Unusual Fire & Explosion Hazards: Material may Burn, but will not ignite readily

5. Health Effects Data

Eye Effects: Solid material is not expected to be an eye irritant; however, contact with molten wax may cause thermal burns. Vapors from molten wax may cause watering of the eyes. Skin effects: Solid material is not expected to be a skin irritant; however, skin contact with molten wax may cause thermal burns. No harmful effects from skin absorption are expected. Inhalations: Vapors emitted from molten wax are expected to have a low degree of irritation by inhalation. Ingestion: No Harmful effects expected. Human Effects of Overexposure: Effects of overexposure my include irritation of the nose and throat.

6. Emergency and first Aid Procedures

Eye Contact: if irritation or redness develops from exposure of fumes generated during hot-melt processing operations, move victim away from exposure and into fresh air. Flush eyes with clean water. If irritation or redness persists, seek medical attention. For contact with the molten material, gently open eyelids and flush affected eyes with cold water, seek immediate medical attention. Skin contact: For contact with molten material, leave material on skin and flush or immerse affected areas using cold water. Seek medical attention. Ingestion: If respiratory symptoms develop from exposure to fumes emitted by the molten material, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop. Oxygen should be administered by qualified personnel. See immediate medical attention

Employee Protection Recommendations

Eye Protection: Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended. A Source of clean water should be available in the work area for flushing eyes and skin. Skin Protection: Not normally required for solid material. The use of thermally-resistant gloves is recommended when there is a potential for exposure to molten wax. Respiratory Protection: No respiratory protection is required when working with the solid material. If airborne concentrations of wax fumes, generated from molten wax are expected, a NIOSH/MSHA approved air purifying respirator with a dust/mist/fume filter should be used. Protection guide). Use a positive-pressure-sir-supplied respirator if there is a potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. A respiratory-protection program that meets OSHA's 29 CFR 1910.34 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

7. Reactivity Data

Stability: Stable under normal conditions of storage and handling. Polymerization: Will not occur Incompatibility (materials to avoid): Avoid contact with strong oxidizing agents. Hazardous Decomposition Products: Combustion can yield major amounts of oxides of carbon and minor amounts of oxides of sulfur and nitrogen.

Conditions of Avoid all possible sources of ignition

8. Accidental Release Measures

This material may burn but will not ignite readily keep all sources of ignition away from spill/release. Prevent spilled material from entering sewers, storm drains, other unauthorized treatment drainage systems and natural waterways. Sweep up and package appropriately for disposal.

9. Handling and storage

Handling: Wash thoroughly after handling. Do not wear contaminated clothing or shoes. Use good personal hygiene practice. Storage: Keep container(s) tightly closed. Use and store this material in cool, dry, well-ventilated areas away from heat and all sources of ignition.

10. Disposal Considerations

This material if discarded as produced is not a RCRA "listed" or "Characteristic" hazardous waste. Use which results in chemical or physical change or contamination may subject it to hazardous waste regulations regarding the proper disposal of this material.

11. Shipping data

Hazardous class of Division: Not classified as hazardous

12. Regulatory Information

This material contains no chemicals subject to the reporting requirements of SARA 313 and 40 CFR 372. These materials contain no chemicals subject to proposition 65. This material has not been identified as a carcinogen by NTP, IARC, OSHA. No EPA (CERCLA) Reportable Quantity

13. Toxicological information

Please refer to CIR review of fossil and synthetic waxes published in 1983

Notice to Reader

The information contained in this MSDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof.