# **Material Safety Data Sheet**

**Product Name** 

MONT MARTE TWO SEASONS ACRYLIC (ALL COLOURS EXCEPT FOR BLACK)

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name MONT MARTE INTERNATIONAL PTY LTD

Address 27 Pentex Street, Salisbury, Queensland, AUSTRALIA, 4107

 Telephone
 07 3255 5406

 Fax
 07 3255 5409

 Emergency
 13 11 26

Synonym(s) BRILLIANT RED • BURGUNDY • BURNT SIENNA • COBALT BLUE • FAST LIGHT YELLOW • FLESH TINT •

GOLD • IVORY BLACK • LAVENDER • LIGHT BLUE • LIGHT GREEN • LIGHT YELLOW • OLIVE GREEN •

ORANGE RED • PINK • PURPLE • SILVER • TITANIUM WHITE

Use(s) ARTIST PAINT
MSDS Date 16 Nov 2009

## 2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

#### NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No.None AllocatedDG ClassNone AllocatedSubsidiary Risk(s)None AllocatedPacking GroupNone AllocatedHazchem CodeNone AllocatedEPGNone Allocated

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
2-AMINO-2-METHYL-1-PROPANOL	C4-H11-N-O	124-68-5 0.5-1.5%	
2-BROMO-2-NITROPROPANE-1,3-DIOL	C3-H6-Br-N-04	52-51-7	0.01-0.06%
POLYACRYLIC ACID	(C3-H4-O2)x	9003-01-4	40-50%
XANTHYLIUM, 9-(2-CARBOXYPHENYL)-3,6- BIS(DIETHYLAMINO)-, MOLYBDATETUNGSTATEPHOSPHATE	Not Available	1326-03-0	<30%
C.I. PIGMENT ORANGE 13	Not Available	3520-72-7	<30%
C.I. PIGMENT YELLOW 1	C17-H16-N4-O4	2512-29-0	<30%
TITANIUM DIOXIDE	Ti-O2	13463-67-7	<30%
WATER	H2O	7732-18-5	20-30%
C.I. PIGMENT BLUE 29	Na2-O-S-Al2-O3-SiO2	57455-37-5	<20%
IRON (III) OXIDE	Fe2-O3	1309-37-1	<20%
MICA	Not Available	12001-26-2	<20%
CALCIUM 3-HYDROXY-4-[(1-SULPHONATO-2-NAPHTHYL)AZO]-2-NAPHTHOATE	C21-H14-N2-O6-S-Ca	6417-83-0 <15%	
2-[(4-CHLORO-2-NITROPHENYL)AZO]-N-(2- CHLOROPHENYL)-3-OXOBUTYRAMIDE	C16-H12-Cl2-N4-O4	6486-23-3 <10%	
C.I. PIGMENT VIOLET 23	C34-H22-Cl2-N4-O2	6358-30-1	<10%
C.I. PIGMENT YELLOW 42	Fe2-H2-O4	51274-00-1	<10%
COPPER PHTHALOCYANIN	C32-H16-Cu-N8	147-14-8	<10%
PROPYLENE GLYCOL (PROPANE-1,2-DIOL)	C3-H8-O2	57-55-6	1-5%
HYDROXYETHYL CELLULOSE	Not Available	9004-62-0	1-1.5%
PHTHALOCYANINE GREEN	Not Available	1328-53-6	<1%

Page 1 of 5

Reviewed: 16 Nov 2009 Printed: 16 Nov 2009

CHEM ALERT

## MONT MARTE TWO SEASONS ACRYLIC (ALL COLOURS EXCEPT FOR BLACK)

#### 4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to

stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

**Inhalation** If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue

flushing with water until advised to stop by the Poisons Information Centre or a doctor.

**Ingestion** For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once).

Advice to Doctor Treat symptomatically

#### 5. FIRE FIGHTING MEASURES

Flammability Non flammable. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

Fire and Explosion

Treat as per requirements for Surrounding Fires: Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

**Extinguishing** Prevent contamination of drains or waterways.

Hazchem Code None Allocated

## 6. ACCIDENTAL RELEASE MEASURES

**Spillage** 

Use personal protective equipment. Contain spillage, then cover / absorb spill with non-combustible absorbant material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. CAUTION: Spill site may be slippery.

### 7. STORAGE AND HANDLING

Storage

Store in a cool, dry, well ventilated area, removed from oxidising agents, acids and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use.

Handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

#### 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

## **Exposure Stds**

Ingredient	Reference		TWA		STEL	
		ppm	mg/m3	ppm	mg/m3	
Iron oxide fume (Fe2O3) (as Fe)	ASCC (AUS)		5			
Mica	ASCC (AUS)		2.5			
Propane-1,2-diol (particulates only)	ASCC (AUS)		10			
Propane-1,2-diol (total vapour & particulates)	ASCC (AUS)	150	474			
Titanium dioxide (a)	ASCC (AUS)		10			

C.I. PIGMENT YELLOW 42

ES-STEL: 10 mg/m3 (Iron)

ES-TWA: 5 mg/m3 (Iron fume/dust)

Biological Limits No biological limit allocated.

Page 2 of 5

RMT

Reviewed: 16 Nov 2009 Printed: 16 Nov 2009

## MONT MARTE TWO SEASONS ACRYLIC (ALL COLOURS EXCEPT FOR BLACK)

**Engineering Controls** 

Avoid inhalation. Use in well ventilated areas.

PPF Personal Protective Equipment is not required under normal conditions of use. When using large quantities or

where heavy contamination is likely, wear: splash-proof goggles, rubber or PVC gloves and coveralls.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**COLOURED PASTE Appearance** Solubility (Water) **SOLUBLE** Odour **ODOURLESS Specific Gravity NOT AVAILABLE** 7 to 8 % Volatiles NOT AVAILABLE На **NOT AVAILABLE Flammability** NON FLAMMABLE Vapour Pressure Vapour Density **NOT AVAILABLE Flash Point** NOT RELEVANT **Boiling Point** 100°C **Upper Explosion Limit NOT RELEVANT Melting Point NOT AVAILABLE Lower Explosion Limit** NOT RELEVANT

**Evaporation Rate NOT AVAILABLE** 

Density 1.1 g/mL

#### 10. STABILITY AND REACTIVITY

**Chemical Stability** Stable under recommended conditions of storage.

**Conditions to Avoid** Avoid contact with incompatible substances.

**Material to Avoid** Incompatible with oxidising agents (eg. hypochlorites) and acids (eg. nitric acid).

**Hazardous** May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

**Decomposition Products** 

**Hazardous Reactions** Polymerization is not expected to occur.

## 11. TOXICOLOGICAL INFORMATION

**Health Hazard Summary** 

Low toxicity. Use safe work practices to avoid eye or skin contact and inhalation. Due to the product form, an

inhalation hazard is not anticipated with normal use.

Eve Low irritant. Contact may result in irritation, lacrimation and redness.

Inhalation Low irritant. Over exposure may result in irritation of the nose and throat, with coughing. Due to the low vapour

pressure, an inhalation hazard is not anticipated with normal use.

Skin Low irritant. Prolonged or repeated contact may result in mild irritation, rash and dermatitis.

Ingestion Low toxicity. Ingestion may result in gastrointestinal irritation, nausea, vomiting, headache and diarrhoea.

**Toxicity Data** 

2-AMINO-2-METHYL-1-PROPANOL (124-68-5)

LD50 (Ingestion): 2150 mg/kg (mouse) LDLo (Ingestion): 1000 mg/kg (rabbit)

2-BROMO-2-NITROPROPANE-1,3-DIOL (52-51-7)

LC50 (Inhalation): > 5 g/m3/6 hours (rat) LD50 (Ingestion): 180 mg/kg (rat) LD50 (Intraperitoneal): 26 mg/kg (rat) LD50 (Intravenous): 37.4 mg/kg (rat) LD50 (Skin): 1600 mg/kg (rat)

LD50 (Subcutaneous): 116 mg/kg (mouse)

POLYACRYLIC ACID (9003-01-4)

LD50 (Ingestion): 2000 mg/kg (guinea pig) LD50 (Intraperitoneal): 39 mg/kg (mouse) LD50 (Intravenous): 70 mg/kg (mouse) C.I. PIGMENT ORANGE 13 (3520-72-7) LD50 (Ingestion): > 5 g/kg (rat)

TITANIUM DIOXIDE (13463-67-7)

TCLo (Inhalation): 250 mg/m3/6 hours (rat)

IRON (III) OXIDE (1309-37-1)

LDLo (Subcutaneous): 30 mg/kg (dog) COPPER PHTHALOCYANIN (147-14-8) LD50 (Ingestion): > 10 g/kg (rat)

PROPYLENE GLYCOL (PROPANE-1,2-DIOL) (57-55-6)

Page 3 of 5

**RMT** 

Reviewed: 16 Nov 2009 Printed: 16 Nov 2009

## MONT MARTE TWO SEASONS ACRYLIC (ALL COLOURS EXCEPT FOR BLACK)

LD50 (Ingestion): > 2080 mg/kg (quail) LD50 (Intraperitoneal): 6660 mg/kg LD50 (Intravenous): 2600 mg/kg (dog) LD50 (Skin): 20800 mg/kg (rabbit)

LD50 (Subcutaneous): 17370 mg/kg (mouse) LDLo (Intramuscular): 6300 mg/kg (rabbit) LDLo (Subcutaneous): 15500 mg/kg (guinea pig) TDLo (Ingestion): 79 g/kg/56 weeks intermittently (child)

HYDROXYETHYL CELLULOSE (9004-62-0) LDLo (Intravenous): 5.1 g/kg/6 days (woman)

TDLo (Intraperitoneal): 500 mg/kg (mouse 3-7 days pregnant; reproductive effects)

## 12. ECOLOGICAL INFORMATION

**Environment** 

Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

## 13. DISPOSAL CONSIDERATIONS

Waste Disposal For small amounts absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the

manufacturer for additional information if larger amounts are involved.

**Legislation** Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

#### NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name None Allocated

UN No.None AllocatedDG ClassNone AllocatedSubsidiary Risk(s)None AllocatedPacking GroupNone AllocatedHazchem CodeNone AllocatedEPGNone Allocated

## 15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform

Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

Additional Information

ACRYLIC - WATER BASED COMPOUNDS: It should be noted that most water based paints and acrylic or thermoplastic resins may contain small percentage of solvents, usually less than 5%. The solvent is used as a dispersion agent for the resin of choice. This solvent component may present potential respiratory hazards only in poorly ventilated areas or when sprayed. Those individuals with existing skin disorders should avoid direct contact.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

Page 4 of 5

RMT

Reviewed: 16 Nov 2009 Printed: 16 Nov 2009

CHEM ALERT

## MONT MARTE TWO SEASONS ACRYLIC (ALL COLOURS EXCEPT FOR BLACK)

#### **HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

## **Report Status**

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Material Safety Data Sheet ('MSDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this MSDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS.

### **Prepared By**

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794

Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au

> MSDS Date: 16 Nov 2009 End of Report

> > Page 5 of 5 RMT

Reviewed: 16 Nov 2009 Printed: 16 Nov 2009