



Page 1/8

Material Safety Data Sheet

acc. to ISO/DIS 11014

01422-XXXX

Printing date 04/06/2006

Reviewed on 04/06/2006

1 Identification of substance

- **Product details**
- **Trade name:** Montana Gold
- **Article number:** 437960
- **Application of the substance / the preparation:** Lacquer
- **Manufacturer/Supplier:**
MOTIP DUPLI GmbH
Kurt Vogelsang Strasse 6
D-74855 Haßmersheim
Tel.: +49/6266/75-0
- **Information department:** Abteilung Produktsicherheit
- **Emergency information:**
Tel.: +49 6266-75-310
Fax: +49 6266-75-362

2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	acetone ☒ Xi, ☒ F; R 11-36-66-67	10-25%
106-97-8	butane (containing < 0,1 % butadiene (203-450-8)) ☒ F+; R 12	10-25%
123-86-4	n-butyl acetate R 10-66-67	10-25%
74-98-6	propane ☒ F+; R 12	10-25%
141-78-6	ethyl acetate ☒ Xi, ☒ F; R 11-36-66-67	2.5-10%
1330-20-7	xylene ☒ Xn; R 10-20/21-38	2.5-10%
71-36-3	butan-1-ol ☒ Xn; R 10-22-37/38-41-67	≤ 2.5%
64742-94-5	Solvent naphtha (petroleum), heavy arom. ☒ Xn, ☒ N; R 51/53-65-66-67	≤ 2.5%
108-65-6	2-methoxy-1-methylethyl acetate ☒ Xi; R 10-36	≤ 2.5%
64742-95-6	Solvent naphtha (petroleum), light arom. ☒ Xn, ☒ N; R 10-51/53-65-66-67	≤ 0.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

USA
(Contd. on page 2)

Page 2/8

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 04/06/2006

Reviewed on 04/06/2006

Trade name: Montana Gold

(Contd of page 1)

3 Hazards identification

Hazard description:



Xi Irritant
F+ Extremely flammable

Information pertaining to particular dangers for man and environment:

- The product has to be labelled due to the calculation procedure of international guidelines.
- At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
- Warning! Pressurized container.
- Has a narcotizing effect.
- Extremely flammable.
- Irritating to eyes.
- Repeated exposure may cause skin dryness or cracking.
- Vapours may cause drowsiness and dizziness.
- Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- 83.8 % by mass of the contents are flammable
- Keep out of the reach of children.
- Classification system:
- The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.
- NFPA ratings (scale 0 - 4)



Health = 1
Fire = 0
Reactivity = 3

HMIS-ratings (scale 0 - 4)



HEALTH 1 Health = 1
FIRE 0 Fire = 0
REACTIVITY 3 Reactivity = 3

4 First aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.

5 Fire fighting measures

- Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents:
- Water
- Water with full jet
- Protective equipment: No special measures required.

6 Accidental release measures

- Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system

(Contd on page 3)

USA

Item Numbers: 01422-1000, 01422-1010, 01422-1020, 01422-1030, 01422-1040, 01422-1050, 01422-1060, 01422-1070, 01422-1080, 01422-1100, 01422-1130, 01422-1140, 01422-1150, 01422-1160, 01422-1170, 01422-1180, 01422-1190, 01422-1220, 01422-1230, 01422-1240, 01422-1250, 01422-1260, 01422-1270, 01422-1330, 01422-1440, 01422-1500, 01422-1800, 01422-1810, 01422-1910, 01422-1920, 01422-1930, 01422-2020, 01422-2030, 01422-2040, 01422-2050, 01422-2060, 01422-2070, 01422-2080, 01422-2090, 01422-2190, 01422-2220, 01422-2260, 01422-2270, 01422-2280, 01422-2450, 01422-2480, 01422-2500, 01422-2510, 01422-2520, 01422-2530, 01422-2540, 01422-2550, 01422-2560, 01422-2590, 01422-2600, 01422-2620, 01422-2630, 01422-2790, 01422-2950, 01422-2970, 01422-2980, 01422-3010, 01422-3050, 01422-3060, 01422-3070, 01422-3080, 01422-3090, 01422-3100, 01422-3110, 01422-3120, 01422-3360, 01422-3380, 01422-3450, 01422-3510, 01422-3550, 01422-3620, 01422-3660, 01422-3710, 01422-3720, 01422-3730, 01422-3800, 01422-3810, 01422-3900, 01422-3960, 01422-4010, 01422-4020, 01422-4060, 01422-4220, 01422-4230, 01422-4320, 01422-4330, 01422-4440, 01422-4500, 01422-4510, 01422-4520, 01422-4530, 01422-4540, 01422-4550, 01422-4560, 01422-4570, 01422-4580, 01422-4590, 01422-4600, 01422-4610, 01422-4620, 01422-4630, 01422-4710, 01422-4910, 01422-4920, 01422-4930, 01422-5000, 01422-5010, 01422-5020, 01422-5040, 01422-5070, 01422-5110, 01422-5120, 01422-5160, 01422-5230, 01422-5240, 01422-5280, 01422-5350, 01422-5390, 01422-5490, 01422-5760, 01422-5810, 01422-5880, 01422-5950, 01422-5980, 01422-6010, 01422-6030, 01422-6040, 01422-6050, 01422-6060, 01422-6170, 01422-6410, 01422-7000, 01422-7010, 01422-7020, 01422-7030, 01422-7070, 01422-7080, 01422-7100, 01422-7110, 01422-7120, 01422-7160, 01422-7170, 01422-7190, 01422-7220, 01422-7230, 01422-7240, 01422-7260, 01422-7270, 01422-7700, 01422-7750, 01422-7840, 01422-7910, 01422-7920, 01422-7930, 01422-7940, 01422-7950, 01422-7960, 01422-8000, 01422-8010, 01422-8020, 01422-8030, 01422-8040, 01422-8050, 01422-8140, 01422-8260, 01422-8340, 01422-8360, 01422-8440, 01422-8500, 01422-8540, 01422-8600, 01422-8610, 01422-8700, 01422-8800, 01422-9110, 01422-9330, 01422-9500

Page 3/8

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/06/2006

Reviewed on 04/06/2006

Trade name: Montana Gold

(Contd. of page 2)

Do not allow to enter sewers/ surface or ground water.
 Measures for cleaning/collecting:
 Ensure adequate ventilation.
 Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:** Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not gas tight seal receptacle.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone	
PEL	2400 mg/m ³ , 1000 ppm
REL	590 mg/m ³ , 250 ppm
TLV	Short-term value: 1782 mg/m ³ , 750 ppm Long-term value: 1188 mg/m ³ , 500 ppm BEI
106-97-8 butane (containing < 0.1 % butadiene (203-450-8))	
REL	1900 mg/m ³ , 800 ppm
TLV	1900 mg/m ³ , 800 ppm
123-86-4 n-butyl acetate	
PEL	710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm
74-98-6 propane	
PEL	1800 mg/m ³ , 1000 ppm
REL	1800 mg/m ³ , 1000 ppm
TLV	(+508) mg/m ³ , (2500) ppm
141-78-6 ethyl acetate	
PEL	1400 mg/m ³ , 400 ppm
REL	1400 mg/m ³ , 400 ppm
TLV	1440 mg/m ³ , 400 ppm

(Contd. on page 4)

USA

Item Numbers: 01422-1000, 01422-1010, 01422-1020, 01422-1030, 01422-1040, 01422-1050, 01422-1060, 01422-1070, 01422-1080, 01422-1100, 01422-1130, 01422-1140, 01422-1150, 01422-1160, 01422-1170, 01422-1180, 01422-1190, 01422-1220, 01422-1230, 01422-1240, 01422-1250, 01422-1260, 01422-1270, 01422-1330, 01422-1440, 01422-1500, 01422-1800, 01422-1810, 01422-1910, 01422-1920, 01422-1930, 01422-2020, 01422-2030, 01422-2040, 01422-2050, 01422-2060, 01422-2070, 01422-2080, 01422-2090, 01422-2190, 01422-2220, 01422-2260, 01422-2270, 01422-2280, 01422-2450, 01422-2480, 01422-2500, 01422-2510, 01422-2520, 01422-2530, 01422-2540, 01422-2550, 01422-2560, 01422-2590, 01422-2600, 01422-2620, 01422-2630, 01422-2790, 01422-2950, 01422-2970, 01422-2980, 01422-3010, 01422-3050, 01422-3060, 01422-3070, 01422-3080, 01422-3090, 01422-3100, 01422-3110, 01422-3120, 01422-3360, 01422-3380, 01422-3450, 01422-3510, 01422-3550, 01422-3620, 01422-3660, 01422-3710, 01422-3720, 01422-3730, 01422-3800, 01422-3810, 01422-3900, 01422-3960, 01422-4010, 01422-4020, 01422-4060, 01422-4220, 01422-4230, 01422-4320, 01422-4330, 01422-4440, 01422-4500, 01422-4510, 01422-4520, 01422-4530, 01422-4540, 01422-4550, 01422-4560, 01422-4570, 01422-4580, 01422-4590, 01422-4600, 01422-4610, 01422-4620, 01422-4630, 01422-4710, 01422-4910, 01422-4920, 01422-4930, 01422-5000, 01422-5010, 01422-5020, 01422-5040, 01422-5070, 01422-5110, 01422-5120, 01422-5160, 01422-5230, 01422-5240, 01422-5280, 01422-5350, 01422-5390, 01422-5490, 01422-5760, 01422-5810, 01422-5880, 01422-5950, 01422-5980, 01422-6010, 01422-6030, 01422-6040, 01422-6050, 01422-6060, 01422-6170, 01422-6410, 01422-7000, 01422-7010, 01422-7020, 01422-7030, 01422-7070, 01422-7080, 01422-7100, 01422-7110, 01422-7120, 01422-7160, 01422-7170, 01422-7190, 01422-7220, 01422-7230, 01422-7240, 01422-7260, 01422-7270, 01422-7700, 01422-7750, 01422-7840, 01422-7910, 01422-7920, 01422-7930, 01422-7940, 01422-7950, 01422-7960, 01422-8000, 01422-8010, 01422-8020, 01422-8030, 01422-8040, 01422-8050, 01422-8140, 01422-8260, 01422-8340, 01422-8360, 01422-8440, 01422-8500, 01422-8540, 01422-8600, 01422-8610, 01422-8700, 01422-8800, 01422-9110, 01422-9330, 01422-9500

Page 4/8

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/06/2006

Reviewed on 04/06/2006

Trade name: Montana Gold

(Contd. of page 3)

1330-20-7 xylene	
PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm (o-, m-, & p-isomers)
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
71-36-3 butan-1-ol	
PEL	300 mg/m ³ , 100 ppm
REL	Short-term value: C 150 mg/m ³ , C 50 ppm Skin
TLV	61 mg/m ³ , 20 ppm
108-65-6 2-methoxy-1-methylethyl acetate	
WEEL	100 ppm

Additional information: The lists that were valid during the creation were used as basis.

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

Breathing equipment: Not required.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

General Information

Form: Aerosol
Color: According to product specification
Odor: Characteristic

Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Not applicable, as aerosol.

(Contd on page 5)

USA

Page 5/8

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/06/2006

Reviewed on 04/06/2006

Trade name: **Montana Gold**

(Contid. of page 4)

· Flash point:	<i>Not applicable, as aerosol.</i>
· Auto igniting:	<i>Product is not selfigniting.</i>
· Danger of explosion:	<i>In use, may form flammable/explosive vapour-air mixture.</i>
· Explosion limits:	
Lower:	<i>1.2 Vol %</i>
Upper:	<i>13.0 Vol %</i>
· Vapor pressure at 20°C (68°F):	<i>8300.0 hPa (6226 mm Hg)</i>
· Density at 20°C (68°F):	<i>0.98000 g/cm³</i>
· Solubility in / Miscibility with Water:	<i>Not miscible or difficult to mix.</i>
· Solvent content:	
Organic solvents:	<i>79.6 %</i>
VOC-USA	<i>79.6 %</i>
	<i>780.1 g/l</i>
VOC-EU	<i>780.1 g/l / 6.51 lb/gal</i>
· Solids content:	<i>17.0 %</i>

10 Stability and reactivity

- *Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.*
- *Dangerous reactions No dangerous reactions known.*
- *Dangerous products of decomposition: No dangerous decomposition products known.*

11 Toxicological information

- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
- *on the skin: No irritant effect.*
- *on the eye: Irritating effect.*
- **Sensitization: No sensitizing effects known.**
- **Additional toxicological information:**

Irritant

The product shows the following dangers according to internally approved calculation methods for preparations:

12 Ecological information

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

USA

(Contd. on page 6)

Page 6/8

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/06/2006

Reviewed on 04/06/2006

Trade name: Montana Gold

(Contd. of page 5)

13 Disposal considerations

- **Product:**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information· **DOT regulations:**

- **Hazard class:** 2.1
- **Identification number:** UN1950
- **Proper shipping name (technical name):** AEROSOLS, flammable
- **Label:** 2.1

· **Land transport ADR/RID (cross-border):**

- **ADR/RID class:** 2 5F Gases
- **UN-Number:** 1950
- **Description of goods:** 1950 AEROSOLS

· **Maritime transport IMDG:**

- **IMDG Class:** 2
- **UN Number:** 1950
- **Label:** 2.1
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Proper shipping name:** AEROSOLS

· **Air transport ICAO-TI and IATA-DGR:**

- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label:** 2.1
- **Proper shipping name:** AEROSOLS, flammable

15 Regulations

- **Sara**
- **Section 355 (extremely hazardous substances):**
None of the ingredient is listed.

(Contd. on page 7)
USA

Item Numbers: 01422-1000, 01422-1010, 01422-1020, 01422-1030, 01422-1040, 01422-1050, 01422-1060, 01422-1070, 01422-1080, 01422-1100, 01422-1130, 01422-1140, 01422-1150, 01422-1160, 01422-1170, 01422-1180, 01422-1190, 01422-1220, 01422-1230, 01422-1240, 01422-1250, 01422-1260, 01422-1270, 01422-1330, 01422-1440, 01422-1500, 01422-1800, 01422-1810, 01422-1910, 01422-1920, 01422-1930, 01422-2020, 01422-2030, 01422-2040, 01422-2050, 01422-2060, 01422-2070, 01422-2080, 01422-2090, 01422-2190, 01422-2220, 01422-2260, 01422-2270, 01422-2280, 01422-2450, 01422-2480, 01422-2500, 01422-2510, 01422-2520, 01422-2530, 01422-2540, 01422-2550, 01422-2560, 01422-2590, 01422-2600, 01422-2620, 01422-2630, 01422-2790, 01422-2950, 01422-2970, 01422-2980, 01422-3010, 01422-3050, 01422-3060, 01422-3070, 01422-3080, 01422-3090, 01422-3100, 01422-3110, 01422-3120, 01422-3360, 01422-3380, 01422-3450, 01422-3510, 01422-3550, 01422-3620, 01422-3660, 01422-3710, 01422-3720, 01422-3730, 01422-3800, 01422-3810, 01422-3900, 01422-3960, 01422-4010, 01422-4020, 01422-4060, 01422-4220, 01422-4230, 01422-4320, 01422-4330, 01422-4440, 01422-4500, 01422-4510, 01422-4520, 01422-4530, 01422-4540, 01422-4550, 01422-4560, 01422-4570, 01422-4580, 01422-4590, 01422-4600, 01422-4610, 01422-4620, 01422-4630, 01422-4710, 01422-4910, 01422-4920, 01422-4930, 01422-5000, 01422-5010, 01422-5020, 01422-5040, 01422-5070, 01422-5110, 01422-5120, 01422-5160, 01422-5230, 01422-5240, 01422-5280, 01422-5350, 01422-5390, 01422-5490, 01422-5760, 01422-5810, 01422-5880, 01422-5950, 01422-5980, 01422-6010, 01422-6030, 01422-6040, 01422-6050, 01422-6060, 01422-6170, 01422-6410, 01422-7000, 01422-7010, 01422-7020, 01422-7030, 01422-7070, 01422-7080, 01422-7100, 01422-7110, 01422-7120, 01422-7160, 01422-7170, 01422-7190, 01422-7220, 01422-7230, 01422-7240, 01422-7260, 01422-7270, 01422-7700, 01422-7750, 01422-7840, 01422-7910, 01422-7920, 01422-7930, 01422-7940, 01422-7950, 01422-7960, 01422-8000, 01422-8010, 01422-8020, 01422-8030, 01422-8040, 01422-8050, 01422-8140, 01422-8260, 01422-8340, 01422-8360, 01422-8440, 01422-8500, 01422-8540, 01422-8600, 01422-8610, 01422-8700, 01422-8800, 01422-9110, 01422-9330, 01422-9500

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/06/2006

Reviewed on 04/06/2006

Trade name: Montana Gold

(Contd. of page 6)

Section 313 (Specific toxic chemical listings):		
1330-20-7	xylene	
71-36-3	butan-1-ol	
TSCA (Toxic Substances Control Act):		
67-64-1	acetone	
106-97-8	butane (containing < 0.1 % butadiene (203-450-8))	
123-86-4	n-butyl acetate	
74-98-6	propane	
141-78-6	ethyl acetate	
1330-20-7	xylene	
13463-67-7	titanium dioxide	
71-36-3	butan-1-ol	
64742-94-5	Solvent naphtha (petroleum), heavy arom.	
108-65-6	2-methoxy-1-methylethyl acetate	
64742-95-6	Solvent naphtha (petroleum), light arom.	
8052-41-3	Stoddard solvent	
14808-60-7	Quartz (SiO ₂)	
Proposition 65		
Chemicals known to cause cancer:		
None of the ingredients is listed.		
Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		
Chemicals known to cause developmental toxicity:		
None of the ingredients is listed.		
Carcinogenicity categories		
EPA (Environmental Protection Agency)		
67-64-1	acetone	D
1330-20-7	xylene	D
71-36-3	butan-1-ol	D
IARC (International Agency for Research on Cancer)		
1330-20-7	xylene	3
13463-67-7	titanium dioxide	3
14808-60-7	Quartz (SiO ₂)	1
NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K
TLV (Threshold Limit Value established by ACGIH)		
67-64-1	acetone	A4
1330-20-7	xylene	A4
13463-67-7	titanium dioxide	A4
14808-60-7	Quartz (SiO ₂)	A2
MAK (German Maximum Workplace Concentration)		
14808-60-7	Quartz (SiO ₂)	1
NIOSH-Ca (National Institute for Occupational Safety and Health)		
13463-67-7	titanium dioxide	
14808-60-7	Quartz (SiO ₂)	

(Contd. on page 8)

USA

Hem Numbers: 01422-1000, 01422-1010, 01422-1020, 01422-1030, 01422-1040, 01422-1050, 01422-1060, 01422-1070, 01422-1080, 01422-1100, 01422-1130, 01422-1140, 01422-1150, 01422-1160, 01422-1170, 01422-1180, 01422-1190, 01422-1220, 01422-1230, 01422-1240, 01422-1250, 01422-1260, 01422-1270, 01422-1330, 01422-1440, 01422-1500, 01422-1800, 01422-1810, 01422-1910, 01422-1920, 01422-1930, 01422-2020, 01422-2030, 01422-2040, 01422-2050, 01422-2060, 01422-2070, 01422-2080, 01422-2090, 01422-2190, 01422-2220, 01422-2260, 01422-2270, 01422-2280, 01422-2450, 01422-2480, 01422-2500, 01422-2510, 01422-2520, 01422-2530, 01422-2540, 01422-2550, 01422-2560, 01422-2590, 01422-2600, 01422-2620, 01422-2630, 01422-2790, 01422-2950, 01422-2970, 01422-2980, 01422-3010, 01422-3050, 01422-3060, 01422-3070, 01422-3080, 01422-3090, 01422-3100, 01422-3110, 01422-3120, 01422-3360, 01422-3380, 01422-3450, 01422-3510, 01422-3550, 01422-3620, 01422-3660, 01422-3710, 01422-3720, 01422-3730, 01422-3800, 01422-3810, 01422-3900, 01422-3960, 01422-4010, 01422-4020, 01422-4060, 01422-4220, 01422-4230, 01422-4320, 01422-4330, 01422-4440, 01422-4500, 01422-4510, 01422-4520, 01422-4530, 01422-4540, 01422-4550, 01422-4560, 01422-4570, 01422-4580, 01422-4590, 01422-4600, 01422-4610, 01422-4620, 01422-4630, 01422-4710, 01422-4910, 01422-4920, 01422-4930, 01422-5000, 01422-5010, 01422-5020, 01422-5040, 01422-5070, 01422-5110, 01422-5120, 01422-5160, 01422-5230, 01422-5240, 01422-5280, 01422-5350, 01422-5390, 01422-5490, 01422-5760, 01422-5810, 01422-5880, 01422-5950, 01422-5980, 01422-6010, 01422-6030, 01422-6040, 01422-6050, 01422-6060, 01422-6170, 01422-6410, 01422-7000, 01422-7010, 01422-7020, 01422-7030, 01422-7070, 01422-7080, 01422-7100, 01422-7110, 01422-7120, 01422-7160, 01422-7170, 01422-7190, 01422-7220, 01422-7230, 01422-7240, 01422-7260, 01422-7270, 01422-7700, 01422-7750, 01422-7840, 01422-7910, 01422-7920, 01422-7930, 01422-7940, 01422-7950, 01422-7960, 01422-8000, 01422-8010, 01422-8020, 01422-8030, 01422-8040, 01422-8050, 01422-8140, 01422-8260, 01422-8340, 01422-8360, 01422-8440, 01422-8500, 01422-8540, 01422-8600, 01422-8610, 01422-8700, 01422-8800, 01422-9110, 01422-9330, 01422-9500

Page 8/8

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/06/2006

Reviewed on 04/06/2006

Trade name: Montana Gold

(Contd. of page 7)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**



Xi Irritant
F+ Extremely flammable

· **Risk phrases:**

Extremely flammable.
Irritating to eyes.
Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

Keep out of the reach of children.
Keep container in a well-ventilated place.
Keep away from sources of ignition - No smoking.
Do not breathe aerosol.
Avoid contact with eyes.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Take precautionary measures against static discharges.
In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
If swallowed, seek medical advice immediately and show this container or label.
Use only in well-ventilated areas.
This material and its container must be disposed of as hazardous waste.
If swallowed, rinse mouth with water (only if the person is conscious).

· **Special labeling of certain preparations:**
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
83.8 % by mass of the contents are flammable
Keep out of the reach of children.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS: Abteilung Labor/QS**

· **Contact:**

Ernst Kast
Motip Dupli GmbH

· *** Data compared to the previous version altered.**

USA